

Shark ADBLUE



RELIABLE
EFFICIENT
MULTI-PURPOSE



Reliable

The Shark AdBlue® dispenser is renowned across the world for its high quality and reliability. All units can be operated manually, i.e. separately and/or in automatic mode.



Efficient

The Shark AdBlue® is equipped with a high-quality Japanese TATSUNO hydraulic system and an efficient electronic meter. It offers an exceptional lifetime.



Multi-purpose

The Shark AdBlue® is suitable for use in garages, workshops and public service stations for road vehicles, where the temperature does not drop below zero.

Shark ADBLUE

+ PRODUCT

- TATSUNO high-precision hydraulic system (made in Japan) with long lifetime
- PDEX and TBELTx reliable electronic meters
- LCD displays (7-6.5-5) with controlled LED backlight
- 2 options - JUNIOR (1 hose) and ECONOMY (2 hoses)

SPECIFICATIONS

- TATSUNO (made in Japan) high-accuracy pulse sensors
- Electronic and electro-mechanical totalisers for each nozzle
- Infra-red controller to adjust the unit
- Preset control valves
- Switching between 40L / min and 5L / min (passenger/ freight)
- Preset volume function / volume on the support
- ELAFLEX dispenser hose and nozzle
- Colours can be customised to suit the client's wishes

TECHNICAL SPECIFICATIONS

Pump capacity : 40 L/min (lorries) 10 L/min (cars)

Precision : $\pm 0.25\%$ (min. 2 litres)

Maximum operating pressure : 0.4 MPa


Resource : 32.5% aqueous urea solution

Power : 230V + 10% -15%, 50Hz max.150VA


Power for switching elements (valves, contactors) : 230V, 50Hz

Ambient temperature : 0°C + 55°C


Fluid temperature : 0°C + 30°C




BMP511.SD/AdB (Junior)
1 AdBlue hose



BMP511.SD-HS/AdB (Junior)
1 + AdBlue hose with spring hinge



BMP522.SXD/AdB (Economy)
2 AdBlue hoses



BMP522.SXD-HS/AdB (Economy)
2+ AdBlue hoses with spring supports

ADBLUE DISPENSERS

1 or 2 hoses, height 1400 mm AdBlue® - Solution 32.5% urea and water, 2 designs - JUNIOR (1 hose), ECONOMY (2 hoses) designed for environments where temperature is higher than 0°C

OPTIONS

- Nozzle options for cars or lorries
- Suspended hose with spring suspension option

STANDARDS

Appliance complies with the technical requirements presented in the harmonised standard and in the CE directives

- OIML R 117 The International Organization of Legal Metrology
- WELMEC 7.2 Software guide (2014/32/EU Measuring Instruments Directive) also applicable to 2004/22/EU
- WELMEC 10.6 Guide for Sealing of Fuel Dispensers (systems for measuring liquids other than water) - 104Kb
- EU declaration of conformity model BMP512.SD/AdB, certificate number 13896/18

CONTACT

44, avenue Lucien Victor Meunier - 33530 Bassens - France
Tél. +33 (0)5 57 80 80 80 - Fax. 05 56 31 61 21 - Email. contact@lafon.fr
WWW.LAFON.FR

ISO 9001 ISO 14001

Non-contractual document
08/2020 39000304 Ind B UK

LAFON MADIC
a company of
group