





#### Robust

Designed for intensive 24h/24h use. Stainless steel housing, chassis with Aluzinc steel doors, (polyester paint) to withstand the weather.



#### Modular

Simple mono-product that adapts to all situations: single or double-face, flow of 40 l/min or 70 l/min in suction or pressure with ZVA nozzle.




### **Efficient**


MADIC industries ML80 high precision meter. MADIC industries GDL80 hydraulic group. MADIC industries TWIN electronic calculator, latest generation (IFSF connection as standard).

## **BOXTER 10 VP**

# + PRODUCT

- Simplified maintenance for a customer service without interruption
- Optimise the profitability of your station
- Proven components
- Reduced cost of use and maintenance





#### **GDL80 PUMPING GROUP**

- · Deaerator
- · Filter cartridge (stainless steel grill) · Service pressure: 0.16 - 0.25 MPa
- · Maximum vacuum : 0.054 MPa
- · Flow rate: 5 to 90 l/min
- · Repeatability: <0.1%
- · Rotation speed: 1500 rpm
- · Suction capacity: >4 metres
- · Noise: <75 dB
- · Three-phase electric motor, 400 V, 50 Hz 0.75 Kw

#### TWIN CALCULATOR

- · A liquid crystal LCD display
- · High visibility backlighting
- · Indication of the amount, volume, unit price, and pump status
- · Automatic reset to zero when the nozzle is taken off-hook
- · The communication protocol is for IFSF

#### OTHER SPECIFICATIONS

- · Automatic ZVA Type M nozzle
- · Brittle couplings
- · Useful flexible length: 4 metres
- · Standard EN 1360 hose
- · Bodywork in bright finish stainless steel
- · Doors in Aluzinc steel with polyester paint
- · Stainless steel connection sleeve included (suction)
- · Colouring according to the graphic chart

#### **OPTIONS**

- · Discharge or suction
- · Flexible support rod
- · 316L stainless steel
- · Flow selection button 40-70 l/min
- · Satellite connection
- · Electromechanical totalisers
- · Prepayment solenoid valves
- · Predetermination touch keyboard (0 9 buttons)
- · Single-phase motor 220V
- · Emergency hand pump
- · Hose greater than 4 metres length
- · Viewing glass

#### **STANDARDS**

- $\cdot$  2006/42/CE (Machine Directive ) relative to the safety of machinery
- · 2014/35/UE (Low Voltage Directive) relative to the electrical safety of Low Voltage electrical equipment
- · 2014/30/UE (EMC Directive) relative to the electromagnetic compatibility
- · 2014/32/UE (MID Directive) Measuring Instruments, EC examination certificate number LNE-20520
- · 2014/34/UE (ATEX Directive) relating to the use of equipment in an explosive atmosphere Technical File presented to the O.N. INERIS under the number INERIS EQUEN 025351/21
- · 94/62/CE regarding packaging and packaging waste
- · EN 13617-1 August 2012, Service stations Construction and characteristics of the fuel distributors
- · NF EN 60204-1 September 2006 Safety of machinery, electrical machinery equipment





Non-contractual document

